

## Allied Telesis AT-CM301 network card Internal Ethernet 100 Mbit/s

**Brand :** Allied Telesis

**Product code:** AT-CM301


**Product name :** AT-CM301

AT-CM301 - 10/100TX, 100FX (ST, 2km) Convertheon™ media and rate converter line card with OAM and Jumbo Frame support, 5.5 W

Allied Telesis AT-CM301 network card Internal Ethernet 100 Mbit/s:

This media and rate converter line card features a 10/100TX twisted pair port and a 100FX optical port. The twisted pair has an RJ-45 connector and a maximum operating distance of 100 meters (328 feet) when connected to an Ethernet or Fast Ethernet device. They operate in full or half-duplex mode, and allow you to build an affordable network, avoiding the cost of terminating fiber cables. The AT-CM301 has a multi mode fiber ST connector and operates up to 2km.

Allied Telesis AT-CM301. Internal. Connectivity technology: Wired, Host interface: PC Card, Interface: Ethernet. Maximum data transfer rate: 100 Mbit/s. Product colour: Silver



| Ports & interfaces                |                                                | Power                             |                           |
|-----------------------------------|------------------------------------------------|-----------------------------------|---------------------------|
| Connectivity technology *         | Wired                                          | Power consumption (typical)       | 5.5 W                     |
| Host interface *                  | PC Card                                        | <b>Operational conditions</b>     |                           |
| Interface *                       | Ethernet                                       |                                   |                           |
| Network                           |                                                |                                   |                           |
| Maximum data transfer rate *      | 100 Mbit/s                                     |                                   |                           |
| Networking standards *            | IEEE 802.1Q, IEEE 802.3ah, IEEE 802.3u         |                                   |                           |
| Ethernet LAN                      | ✓                                              | Operating temperature (T-T)       | 0 - 40 °C                 |
| Wi-Fi                             | ✗                                              | Storage temperature (T-T)         | -25 - 70 °C               |
| Full duplex                       | ✓                                              | Operating relative humidity (H-H) | 5 - 95%                   |
| Jumbo frames support              | ✓                                              | Storage relative humidity (H-H)   | 5 - 95%                   |
| Maximum operating distance        | 100 m                                          | Operating altitude                | 0 - 3048 m                |
| Design                            |                                                | Weight & dimensions               |                           |
| Component for *                   | PC                                             | Width                             | 22 mm                     |
| Product colour                    | Silver                                         | Depth                             | 73 mm                     |
| Internal *                        | ✓                                              | Height                            | 130 mm                    |
| LED indicators                    | LAN, Power                                     | Weight                            | 113 g                     |
| Mean time between failures (MTBF) | 1500000 h                                      | Other features                    |                           |
| Safety                            | UL 60950-1 (cULUS), EN-60950-1 (TUV), EN-60825 | Compliance industry standards     | IEEE 802.3u, IEEE 802.3ah |
| Certification                     | FCC, EN-55022, VCCI, C-Tick, CE.               | Flow control support              | ✓                         |
|                                   |                                                | Dimensions (WxDxH)                | 22 x 73 x 130 mm          |
|                                   |                                                | Networking features               | Fast Ethernet             |
|                                   |                                                | Ports quantity                    | 1                         |
|                                   |                                                | Link/Act LED                      | ✓                         |
|                                   |                                                | Wireless connection               | ✗                         |



0767035189109



767035189109

### Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.